



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/537,754	03/30/2000	Yong-Ha Hwang	1316.1042	8427

21171 7590 11/04/2003

STAAS & HALSEY LLP
SUITE 700
1201 NEW YORK AVENUE, N.W.
WASHINGTON, DC 20005

EXAMINER

LE, KIMLIEN T

ART UNIT	PAPER NUMBER
----------	--------------

2653

DATE MAILED: 11/04/2003

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary

Application No.

09/537,754

Applicant(s)

HWANG, YONG-HA

Examiner

Kimlien T Le

Art Unit

2653

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
- Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 08 August 2003.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-3, 6-12, 14-20 and 22-28 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-3, 6-12, 14-20 and 22-28 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
- 11) ☐ The proposed drawing correction filed on _____ is: a) ☐ approved b) ☐ disapproved by the Examiner.
If approved, corrected drawings are required in reply to this Office action.
- 12) ☐ The oath or declaration is objected to by the Examiner.

Priority under 35 U.S.C. §§ 119 and 120

- 13) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
a) ☒ All b) ☐ Some * c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
* See the attached detailed Office action for a list of the certified copies not received.
- 14) ☐ Acknowledgment is made of a claim for domestic priority under 35 U.S.C. § 119(e) (to a provisional application).
a) ☐ The translation of the foreign language provisional application has been received.
- 15) ☐ Acknowledgment is made of a claim for domestic priority under 35 U.S.C. §§ 120 and/or 121.

Attachment(s)

- 1) ☐ Notice of References Cited (PTO-892) 4) ☐ Interview Summary (PTO-413) Paper No(s). _____
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948) 5) ☐ Notice of Informal Patent Application (PTO-152)
- 3) ☐ Information Disclosure Statement(s) (PTO-1449) Paper No(s) _____ 6) ☐ Other: _____

Response to Arguments

Applicant's arguments filed on August 1, 2003 have been fully considered but they are not deemed to be persuasive.

Applicant asserts on page 5 :

However, nothing is taught or suggested in Nomura as to detecting an amplitude of the envelope signal by "sampling the envelope signal between a maximum value and a minimum value into n sample signals at a zero cross interval, and obtaining an average value of the obtained n peak-to-peak values," as recited in independent claim 1.

The Examiner maintains that Nomura (U.S. Patent 6,298,024) discloses that Nomura shows detecting an amplitude of the envelope signal by "sampling the envelope signal between a maximum value and a minimum value into n sample signals at a zero cross interval, and obtaining an average value of the obtained n peak-to-peak values (column 5, lines 35-40; column 15, lines 10-40).

Nomura fails to teach or suggest, "a controller detecting an amplitude of the envelope signal at an off-track state of the loaded disc, and discriminates the type of the loaded disc using the detected amplitude, wherein said controller comprises: an envelope amplitude detector detecting the amplitude of the envelope signal and sampling the envelope signal between a maximum value and a minimum value into n sample signals at a zero cross interval, and obtaining an average value of the obtained n peak-to-peak values as the detected amplitude.

The Examiner maintains that Nomura (U.S. Patent 6,298,024) discloses in Figs. 5(a) and 5(b) that the average is taken over a zero cross interval (between the top and bottom values).

Also, Applicant asserts on pages 5 and 6 :

Nomura is silent as to teaching or suggesting "a disc discriminator comparing a level of the detected amplitude with at least one predetermined reference level," emphasis added, as recited in independent claim 1.

Art Unit: 2653

The Examiner maintains that Nomura (U.S. Patent 6,298,024) shows the predetermined reference level (Fig. 3, numeral 34. See also column 7 lines 1-13).

Moreover, Applicant asserts on page 6 :

Contrary to the assertions made in the Office Action that in Nomura "TES is tracking error signal that are used to control the position of the light beam to follow a target information track -off-track or on-track," Nomura specifically indicates that the type of disc is discriminated on on track only.

The Examiner maintains that Nomura (U.S. Patent 6,298,024) shows that it is off tracks (This is happening across tracks).

Claim Rejections - 35 USC § 102

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

Claims 1-3,6-12,14-20 and 22-28 are rejected under 35 U.S.C. 102(e) as being anticipated by Nomura(US 6,298,024).

Regarding claim 1, see Figs. 1 , 2 and 3 of Nomura which show an optical disc discrimination apparatus for use in an optical disc reproducer which reproduces data from a plurality of different types of discs with a single optical pickup, the optical disc discrimination apparatus comprising: a RF envelope generator (10) which generates an

Art Unit: 2653

envelope signal from an RF signal read from one of the discs (1) which is loaded in the optical disc reproducer(11); and a controller (12,22) which detects an amplitude of the envelope signal at an off-track state of the loaded disc, and discriminates the type of the loaded disc using the detected amplitude (column 9 line 45- column 10 line 65), wherein the controller comprises: an envelope amplitude detector detecting the amplitude of the envelope signal and sampling the envelope signal between a maximum value and a minimum value into n sample signals at a zero cross interval, and obtaining an average value of the obtained n peak-to peak values as the detected amplitude (column 3, lines 19-45); and a disc discriminator which compares a level of the detected amplitude with at least one predetermined reference level and discriminates whether the loaded disc is a CD, a DVD ROM, or a DVD-RAM, based on the comparison (column 1, lines 47-60).

With regard to claim 2, see Figs. 1, 2 and 3 of Nomura which show an optical disc discrimination apparatus of claim 1, wherein the RF envelope generator (10) generates the envelope signal by a peak hold and a bottom hold of the RF signal read from the loaded disc (column 5, line 66 - column 6, line 22).

With regard to claim 3, see Figs. 1, 2 and 3 of Nomura which show the optical disc discrimination apparatus of claim 1, wherein the off-track state is a state where only a focusing is accomplished before a tracking control of the loaded disc is performed (column 9, line 49 - 54; column 10, line 45 - 47; column 10, line 57 -65 ; column 23, line 24 - 26).

Regarding claims 8 and 9, see Figs. 1, 2 and 3 of Nomura which show all the features of claim 1. Also, Nomura shows that the envelope amplitude detector detects a

Art Unit: 2653

magnitude of peak-to-peak values of the n sample signals, and obtains the average value of the peak-to-peak values to determine the detected amplitude (column 15, lines 10-40).

With regard to claim 6, see Figs. 1, 2 and 3 of Nomura which show the optical disc discrimination apparatus of claim 1, wherein the at least one predetermined reference level is set based on conditions that a CD has a track pitch relatively larger than a DVD-ROM, thus having a larger change in the amplitude of the RF signal as an optical beam emitted by the optical disc reproducer traverses tracks thereof, and that a DVD RAM has no change in the amplitude of the RF signal as the optical beam emitted by the optical disc reproducer traverses the tracks thereof (column 3, lines 45-60).

With regard to claim 7, see Figs. 1, 2 and 3 of Nomura which show the optical disc discrimination apparatus of claim 6, wherein the disc discriminator discriminates whether: the loaded disc is the CD if a level of the detected envelope amplitude is larger than a first one of the at least one predetermined reference level; the loaded disc is the DVD-ROM if the level of the detected envelope amplitude is smaller than the first predetermined reference level and larger than a second one of the at least one predetermined reference level; and the loaded disc is the DVD-RAM if the level of the detected envelope amplitude is smaller than the second predetermined reference level (column 10, lines 1-25).

With regard to claims 10 and 18, Nomura shows all the features of claims 3 or 12. Also, Nomura show that the controller controls rotation of the loaded disc at a speed slow enough to maintain a focusing state with respect to each of the plurality of different types of discs in the off-track state (column 11, lines 14-27).

Art Unit: 2653

With regard to claim 11, see Figs. 1, 2 and 3 of Nomura which show the optical disc discrimination apparatus of claim 4, wherein the controller controls rotation of the loaded disc at a speed slow enough to maintain a focusing state with respect to each of the CD, DVD-ROM and DVD-RAM in the off-track state (column 1, lines 55-60; column 10, lines 24-27).

With regard to claim 12, see Figs. 1, 11 and 12b of Nomura which show an optical disc discrimination method of discriminating a type of a disc for use in an optical disc reproducer which reproduces data from a plurality of discs with only a single optical pickup, the optical disc discrimination method comprising: (a) obtaining an envelope signal from a RF signal detected from one of discs which is loaded in the optical disc reproducer at an off-track state of the loaded disc; (b) detecting an amplitude of the envelope signal comprising: sampling the envelope signal between a maximum value and a minimum value into n sample signals at a zero cross interval, detecting the amplitude of the envelope signal, and obtaining an average value of the obtained n peak-to-peak values as the detected amplitude (column 3, lines 19-45); (c) comparing the amplitude of the envelope signal with at least one predetermined reference level; and (d) discriminating whether the loaded disc is a CD, a DVD-ROM, or a DVD-RAM based on the comparison (column 3, lines 19-45; column 6, lines 1-20).

With regard to claims 14 and 15, see Figs. 5(a), (b), (c) and 6(b) of Nomura which show the optical disc discrimination method of claim 12, wherein the step (d) comprises discriminating the loaded disc as the CD, the DVD-ROM or the DVD-RAM, based upon a condition that a change in the RF signal amplitudes as an optical beam of the optical disc reproducer moves across tracks thereof differs from each other in

Art Unit: 2653

the CD, the DVD, ROM, and the DVD-RAM, wherein a first one of the at least one predetermined reference level is larger than the amplitude of the RF signal detected from the CD, and a second one of the at least one predetermined reference level is smaller than the first predetermined reference level and larger than the amplitude of the RF signal detected from the DVD-ROM (column 10, lines 10-20).

With regard to claims 16 and 17, see Figs. 1, 11 and 12b of Nomura which show the optical disc discrimination method of claim 13, wherein the detecting of the predetermined number of sample signals comprises detecting a magnitude of peak-to-peak values of the predetermined number of samples; and the obtaining of the average value comprises obtaining the average value of the peak-to-peak values to detect the amplitude of the envelope signal (column 15, lines 10-40).

With regard to claims 19, see Figs. 1, 11 and 12b of Nomura which show the optical disc discrimination method of claim 12, further comprising controlling a rotation of the loaded disc at a speed slow enough to maintain a focusing state with respect to each of the plurality of different types of discs in the off-track state (column 1, lines 55-60; column 10, lines 24-27).

With regard to claim 20, see Figs. 1, 2 and 3 of Nomura which show an optical reproducer which reproduces data from a plurality of different types of discs using a single optical pickup, the optical disc discrimination apparatus comprising: a data reproducing device (4) which reproduces the data by illuminating an optical beam on a loaded one of the optical discs, receive the reflected optical beam, to generate an RF signal; an RF envelope generator (20,21) which generates an envelope signal from the RF signal; and a controller (22) which detects an amplitude of the envelope signal only when

Art Unit: 2653

a focusing operation of the disc being performed prior to a tracking control operation of the disc is being performed, to discriminate the type of the loaded disc, wherein the controller controls the reproduction of the disc in accordance with the discriminated disc type(column 9 line 45- column 10 line 65).

With regard to claim 22, see Figs. 1, 2 and 3 of Nomura which show the optical reproducer of claim 20, wherein the controller (12) controls rotation of the loaded disc at a speed slow enough to maintain a focusing state with respect to each of the plurality of different types of discs during the focusing operation (column 9, lines 49-54).

With regard to claim 23, see Figs. 1, 2 and 3 of Nomura which show the optical reproducer of claim 20, optical reproducer of claim 20, wherein the optical beam is initialized to 635-650 nm during the focusing operation of the disc performed prior to the tracking control operation of the disc (column 9, lines 49-54).

With regard to claim 24, see Figs. 1, 2 and 3 of Nomura which show the optical reproducer of claim 20, further comprising: an RF amplifier(201,211) to amplify the RF signal output from the data reproducing device; a focusing servo (7)to output a focus control signal in accordance with a focus error signal of the RF signal and the discriminated disc type; a pickup actuator (4) to drive the data reproducing device for focusing based upon the focus control signal; a spindle motor to rotate the loaded disc in accordance with a servo control signal; and a spindle servo to generate the servo control signal in accordance with the discriminated disc type and the amplified RF signal.

With regard to claim 25, see Figs. 1, 2 and 3 of Nomura which show the optical disc reproduction method of reproducing data from a plurality of different types of discs using a single optical pickup, the optical disc reproduction method comprising:

Art Unit: 2653

reproducing the data by illuminating an optical beam on a loaded one of the optical discs, receive the reflected optical beam, to generate an RF signal; generating an envelope signal from the RF signal; and detecting an amplitude of the envelope signal only when a focusing operation of the disc being performed prior to a tracking control operation of the disc is being performed, to discriminate the type of the loaded disc, and controlling the reproduction of the disc in accordance with the discriminated disc type(column 9 line 45- column 10 line 65).

With regard to claim 26, see Figs. 1, 2 and 3 of Nomura which show the optical disc reproduction method of claim 25, wherein the discriminating of the type of disc comprises comparing a level of the detected amplitude with at least one predetermined reference level and discriminating whether the loaded disc is a CD, A DVD-ROM, or a DVD-RAM, based upon the comparison.

With regard to claim 27, see Figs. 1, 2 and 3 of Nomura which show an optical disc reproduction method of claim 25, further comprising controlling rotation of the loaded disc at a speed slow enough to maintain a focusing state with respect to each of the plurality of different types of discs during the focusing operation.

With regard to claim 28, see Figs. 1, 2 and 3 of Nomura which show optical disc reproduction method of claim 25, further comprising initializing the optical beam to 635-650 nm during the focusing operation of the disc performed prior to the tracking control operation of the disc.

Art Unit: 2653

Points of Contact


Any inquiry concerning this communication or earlier communications from the examiner should be directed to Kimlien T Le whose telephone number is 703 305 3498.

The examiner can normally be reached on M-F 8a.m-5p.m.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Korzuch William can be reached on 703 305 6137. The fax phone numbers for the organization where this application or proceeding is assigned are 703 872 9314 for regular communications and 703 872 9314 for After Final communications.

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist whose telephone number is 703 305 3900.

Kimlien Le
October 31, 2003


WILLIAM KORZUCH
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2600